




# DE950TN

**8Ω****HF Drivers - 2.0 Inches**

- 220 W continuous program power capacity
- 2" horn throat diameter
- 75 mm (3 in) aluminium voice coil
- Titanium diaphragm
- 500 - 18000 Hz response
- 108.5 dB sensitivity
- Neodymium magnet assembly with shorting copper cap

# DE950TN

HF Drivers- 2.0 Inches



## SPECIFICATIONS<sup>1</sup>

|  |                |
|--|----------------|
| Throat Diameter                        | 50 mm (2.0 in) |
| Nominal Impedance                      | 8 Ω            |
| Minimum Impedance                      | 8.3 Ω          |
| Nominal Power Handling <sup>2</sup>    | 110 W          |
| Continuous Power Handling <sup>3</sup> | 220 W          |
| Sensitivity <sup>4</sup>               | 108.5 dB       |
| Frequency Range                        | 1.0 - 18.0 kHz |
| Recommended Crossover <sup>5</sup>     | 0.8 kHz        |
| Voice Coil Diameter                    | 75 mm (3.0 in) |
| Winding Material                       | Aluminium      |
| Inductance                             | 0.14 mH        |
| Diaphragm Material                     | Titanium       |
| Flux Density                           | 2.05 T         |
| Magnet Material                        | Neodymium Ring |

## MOUNTING AND SHIPPING INFO

|   |                                     |
|---|-------------------------------------|
| Four M6 holes 90° on 102 mm (4 in) diameter |                                     |
| Overall Diameter                            | 131 mm (5.2 in)                     |
| Depth                                       | 85 mm (3.3 in)                      |
| Net Weight                                  | 2.7 kg (5.9 lb)                     |
| Shipping Units                              | 4                                   |
| Shipping Weight                             | 11.4 kg (25.1 lb)                   |
| Shipping Box                                | 310x165x230 mm (12.20x6.50x9.06 in) |

## REPLACEMENT DIAPHRAGM

MMD3BTN8M

1. Driver mounted on B&C ME 75 horn.
2. 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated nominal impedance.
3. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
4. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
5. 12 dB/oct. or higher slope high-pass filter.