




6" Ceramic Woofer

Program Power	300 W
Rated impedance	8 Ohm
Nominal diameter	6,5" - 165 mm
Sensitivity (2,83V/1m)	90,5 dB
Voice coil diameter	1,5 in - 38 mm
Frequency Range	80-7000 Hz


SPECIFICATIONS

Nominal Diameter	6,5" - 165 mm
Rated Impedance	8 Ohm
AES Power	150 W
Program Power ²	300 W
Sensitivity ³	90,5 dB
Frequency Range ⁴	80-7000 Hz
Minimum Impedance	6 Ohm
Basket Material	Steel
Magnet Material	Ferrite
Cone Material	Treated Paper - Water repellent
Cone Shape	Exponential
Surround	Rubber - Single Roll
Suspension	-
Voice Coil Diameter	1,5 in - 38 mm
Voice Coil Winding Material	Copper
Voice Coil Length	11,5 mm - 0,45 in
Voice Coil Former Material	Glass Fiber
Connection type	Fast-On
Ferrofluid	No
Magnetic Gap Height	6,5 mm - 0,26 in
Max. Peak to Peak Excursion	20 mm - 0,79 in
Efficiency Bandwidth Product EBP	124
Recommended Enclosure Volume	5÷15 lt (dm ³) - 0,18÷0,53 cu.ft

FREQUENCY RESPONSE CURVE ⁶



FREE AIR IMPEDANCE CURVE ⁷



T/S PARAMETERS

8 Ohm

Resonance frequency	Fs	77 Hz
DC Resistance	Re	4,9 Ohm
Mechanical Q Factor	Qms	7,3
Electrical Q Factor	Qes	0,62
Total Q Factor	Qts	0,56
BI Factor	BI	8,7 Tm
Effective Moving Mass	Mms	18 g - 0,04 lb
Equivalent Cas air loaded	Vas	5,6 lt (dm ³) - 0,2 cuft
Effective piston area	Sd	132,7 cm ² - 20,6 sq.in
Max. Linear Excursion ⁵	Xmax	4 mm - 0,16 in
	Xvar	6 mm - 0,24 in
Voice Coil Inductance @ 1kHz	Le	0,38 mH
Half-space Efficiency	η0	0,4 %

NOTES

¹ Nominal power is determined according to AES2-1984 (r2003) standard.

² Program Power is defined as 3 dB greater than the Nominal rating.

³ Sensitivity represents the averaged value of acoustic output as measured on the forward central axis of cone, at distance 1m, when connected to 2,83V sine wave test signal.

⁴ Frequency range is given as the band of frequencies delineated by the lower and upper limits where the output level drops by 10 dB below the rated sensitivity in half space environment.

⁵ Linear Math. Xmax is calculated as (Hvc-Hg)/2 + Hg/4 where Hvc is the coil depth and Hg is the gapdepth.

⁶ Frequency response measured in 260 L reference closed box in free field (4π) with 2.83 Vrms

⁷ Impedance curve is measured in free air conditions at small signals.

MOUNTING AND SHIPPING INFORMATION

Overall Diameter	185,5 mm - 7,3 in
Baffle Cutout Diameter	144 mm - 5,67 in
Flange and Gasket Thickness	4 mm - 0,16 in
Total Depth	87 mm - 3,43 in
Bolt Circle Diameter	168 mm - 6,61 in
Bolt Holes Quantity and Diameter	4 / 5 mm - 0,2 in
Net Weight	1,8 Kg - 3,97 lb
Shipping Weight	2 Kg - 4,4 lb