



HF103

1" - 60 W - 107 dB

NOMINAL SPECIFICATIONS

Throat Diameter	25.4 mm (1 in)
Overall Diameter	100 mm (3.94 in)
180° Mounting Holes Diameter (2xM6)	76 mm (2.99 in)
Depth	55 mm (2.17 in)
Net Weight	1.3 kg (2.9 lb)
Shipping Box	147 x 130 x 82 mm
(Single Carton Box)	(5.8 x 5.1 x 3.2 in)
Shipping Weight	1.6 kg (3.5 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.8 Ω
AES Power above 0.65 kHz (1)	60 W
Maximum Power above 0.9 kHz (2)	120 W
Minimum Crossover Frequency (3)	1.3 kHz
Sensitivity (1W/1m) (4)	107 dB
Frequency Range	1÷20 kHz
Voice Coil Diameter	44 mm (1.73 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Ketone Polymer
Diaphragm Shape	Dome
Winding Depth	2.3 mm (0.09 in)
Magnetic Gap Depth	2.85 mm (0.11 in)
Flux Density	1.5 T
Magnet	Ferrite Ring
Re	5.8 Ω
Phase Plug Design	Annular
NET Air Volume filled by HF Driver	0.33 dm ³ (0.011 ft ³)

NOTE: Driver Mounted on a 1" 50° x 40° Al horn

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3 dB greater than nominal power.

(3) 12 dB/oct or higher slope high-pass filter.

(4) Averaged within the frequency range.

