

# NDX495

## DRIVER

### DESCRIPTION

The 1.75" PKX dome NDX495 is a compression driver for professional applications where high-quality sound and long-term reliability are required. The ultra-compact size and the low recommended crossover point from 1000 Hz make both transducers ideal for small two-way cabinet designs and three-way loudspeaker systems. PKX (modified polyether ether ketone) is a rigid yet lightweight material, optimized with reinforcing ribs, offering remarkable precision and reliability compared with other polymeric materials. The voice coil utilizes ultralight edge wound aluminum wire, class-leading neodymium magnets, a 3-slot phase plug, and a copper ring design to deliver exceptional power handling, sensitivity, and low distortion across its operating bandwidth. The driver specifies 140 Watts of continuous power handling, with a sensitivity of of 109 dB.



### FEATURES

- 1.75-inch PKX dome, polyimide surround
- Kapton former, edge wound aluminum voice coil
- 140W continuous program power handling @ 80
- Frequency range: 500Hz - 20kHz
- 4-slot optimized geometry phase plug
- Copper inductance ring for extended response
- High-flux density neodymium magnet
- Recommended for 2-way speaker design

## TECHNICAL SPECIFICATIONS

<b>General specifications</b>	Exit Throat Diameter:	1.0 inch / 25 mm
	Related Impedance:	8 ohm
	Program Power (watt):	140 W
	Power handling capacity (watt):	70 W
	Sensitivity:	109 dB
	Frequency range:	1200 - 20000 Hz
	Suspension Design:	Flat
	Minimum Impedance (ohm):	6.50 ohm
	Voice Coil Diameter:	1.75 inch / 44 mm
	Voice Coil Former Design:	Straight - Kapton
	Number of layers:	1
	Kind of layers:	outside
	Flux Density:	1.8 T
	Phase Plug Design:	3 slot
<b>Thiele - small parameters</b>	BI factor (BI) (T x m):	7.50 T x m
<b>Mounting information</b>	Overall diameter:	85 mm / 3.35 inches
	Overall height:	44 mm / 1.73 inches
	Mounting:	4 x 6 mm threaded holes at 90°
<b>Standard compliance</b>	Safety agency:	CE compliant
<b>Size</b>	Weight:	0.85 kg / 1.87 lbs
<b>Shipping information</b>	Package Height:	65 mm / 2.56 inches
	Package Width:	111 mm / 4.37 inches
	Package Depth:	113 mm / 4.45 inches
	Package Weight:	0.89 kg / 1.96 lbs

## PART NUMBER

- **15100024**

NDX495

8ohm



