

NERO-15MWN700D

AUDIENCE

15" - Midwoofer - 1400W - 97dB



- Proprietary cone paper material with manila pulp
- Strong neodymium motor
- 3" voice coil with APC (Advanced Polymer Coating)
- Interleaved Sandwich Voice Coil technology
- Cast aluminum chassis
- Minimum damping fiber glass voice coil former
- Copper sleeve for low inductance and reduced distortion
- Vented motor for reduced compression

Dimensions & Weight

Overall Diameter	394 mm (15.5 in)
Bolt Circle Diameter	378 mm (14.87 in)
Baffle Cutout Diameter	361.4 mm (14.22 in)
Mounting Depth	164 mm (6.5 in)
Flange and Gasket Thickness	17 mm (0.7 in)
Net Weight	5.3 Kg (11,7 lb)
Shipping Box	425 x 425 x 232 mm (16.7 x 16.7 x 9.1 in)
Gross Weight	6.8 Kg (15 lb)

Specs :

Nominal Impedance	8 Ohm
Minimum Impedance	5.3 Ohm
AES Power Handling (1)	700 W
Maximum Power Handling (2)	1400 W
Sensitivity (1W/1m)	97 dB
Frequency Range	41 - 5800 Hz
Voice Coil Diameter	75.6 mm (3 in), Interleaved sandwich
Winding Material	Copper
Former Material	Till
Winding Depth	17.8 mm
Magnetic Gap Depth	10 mm (0.4 in)
Flux Density	1.07 T
Magnet	Neodymium
Basket Material	Aluminium die cast
Demodulation	Extended copper cap
Cone Surround	Triple roll with damping glue
NET Air Volume filled by driver	7.78 liters
Spider Profile	Progressive height waves
Weather Resistant	Yes

Thiele Small Parameters

Fs	41.4 Hz
Re	5.4 Ohm
Qes	0.48
Qms	9.07
Qts	0.46
Vas	145.9 liters
Sd	865.7 cm ²
Xmax (3)	7.3 mm
Xdamage (4)	24 mm
Mms	107.6 g
Bl	17.7 Tm
Le	0.37 mH
Cms	0.14 mm/N
Rms	3.1 Kg/s
Eta Zero	2.07 %
EBP	86

NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Xmax= ((Winding depth - magnetic gap depth)/2) +(magnetic gap depth/3)
- (4) Maximum excursion (p-p) before permanent damage
- (5) T/S parameters measured on drive units that are broken in using Klippel LPM Measurement System.

